
Drywall Systems

Double-stitched web for strength and stability, knurled face for easier screw installation, fast and painless installation.


MAIN RUNNER



CROSS TEE



1-1/2" WALL ANGLE



FEATURES AND BENEFITS

- Knurled face for easier screw installation
- Expanded cross tee offering facilitates integration with Types F & G light fixtures
- Double stitched web for added strength
- Cross tees feature staked-on end tabs for optimal tightness and ease of installation
- Manufactured in accordance with ASTM C635 and in compliance with ASTM C645
- Classified Heavy Duty per ASTM C635
- Stepped-end design featured on cross tees

- Utilizes G40 hot-dipped galvanized construction for superior corrosion resistance
- G90 is available for extreme corrosion resistance and exterior applications
- Suitable for use in the following UL/ULC Fire Resistive Assemblies: D501, D502, D503, G041, G523, G524, G526, G527, G528, G529, G553, L502, L508, L513, L515, L525, L526, L529, P506, P508, P509, P510, P513, P514, P560
- Metric sizes available for integration with Gyptone® BIG™ Boards
- High recycled content

LEED® v4

RECYCLED CONTENT

MAIN RUNNER

PRE: 19-28% POST: 34-69% TOTAL: 62-88%

CROSS TEE

PRE: 19-28% POST: 34-68% TOTAL: 62-87%

WALL ANGLE

PRE: 19-28% POST: 34-69% TOTAL: 61-88%

✓ MR: PBT Source Reduction (Healthcare)

MR: Material Ingredients (HPDs)

✓ MR: Sourcing Raw Materials

MR: Environmental Product Declarations

(EPDs)

MR: Construction and Demolition Waste Management Planning


 LEED^* is a registered trademark of the U.S. Green Building Council.

Declare^{ss}

Living Building Challenge Red List Free®

Declare sM is a service mark of The International Living Future Institute

MAIN RUNNER



WALL ANGLE





1-1/2" DRYWALL SYSTEM

Drywall Systems

